

GEMÜ C60 CleanStar

Pneumatically operated diaphragm valve



Features

- High purity due to cleanroom manufacturing
- High Flow version selectable
- High flow rate with low-stress media channelling
- Minimal deadleg
- Optional flow direction
- Also available as T valve
- The valve is available with an ECTFE union nut as an option.
- Reduced costs thanks to long service life

Description

The GEMÜ C60 CleanStar® ultra pure 2/2-way diaphragm valve has a plastic piston actuator and is pneumatically operated. A stroke limiter (not with actuator size 4) and an optical position indicator are integrated as standard. All media wetted parts are made of PFA or PTFE. This High Purity version of the CleanStar® series complies with the strictest purity standards and boasts high chemical resistance. It can also be used with high media temperatures. As such, it is often used at the supply and distribution level in semiconductor factories.

Technical specifications

- **Media temperature :** -10 to 150 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 4 to 50
- **Body configurations:** 2/2-way body | T-body | V valve body
- **Connection types:** Flare | Flare SpaceSaver | Nexus Connect® SpaceSaver | PrimeLock® | PrimeLock® SpaceSaver | Spigot | Super 300 Type Pillar® SpaceSaver | Union end | Welded-on Nexus Connect®
- **Connection standards:** DIN
- **Body materials:** PFA | PP-H, grey | PP-H, natural | PVDF
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration



further information
webcode: GW-C60



Contents

1 CleanStar product line.....	4
2 Product description.....	5
3 Designs.....	6
GEMÜ C60 CleanStar PFA	8
4 Availability C60 PFA.....	9
4.1 Body configuration - 2/2-way body (code D)	9
4.1.1 Materials	9
4.2 Connections.....	10
4.2.1 Body configuration - 2/2-way body (code D).....	10
4.2.2 Body configuration - T body (code T).....	13
5 Order data C60 PFA	14
5.1 Order data - body configuration - 2/2-way body (code D).....	14
5.2 Order data - body configuration - T body (code T)	16
6 Technical data C60 PFA	18
6.1 Medium	18
6.2 Temperature	18
6.3 Pressure	18
6.4 Product conformities	22
6.5 Mechanical data	22
7 Dimensions C60 PFA.....	23
7.1 2/2-way valves (code D).....	23
7.2 T body (code T)	29
7.3 Mounting dimensions	33
GEMÜ C60 CleanStar PFA 3/5-way	34
8 Availability C60 PFA 3/5-way	35
8.1 Connections.....	35
8.2 Actuator assignments.....	35
9 Order data C60 PFA 3/5-way	36
9.1 Order codes	36
9.2 Order example	37
10 Technical data C60 PFA 3/5-way.....	38
10.1 Medium	38
10.2 Temperature	38
10.3 Pressure	38
10.4 Product conformities	40
10.5 Mechanical data	40
11 Dimensions C60 PFA 3/5-way	40
GEMÜ C60 CleanStar PVDF	41
12 Availability Cleanstar C60 PVDF	42

13 Order data C60 PVDF	43
13.1 Order codes	43
13.2 Order example	43
14 Technical data C60 PVDF.....	44
14.1 Medium	44
14.2 Temperature	44
14.3 Pressure	44
14.4 Product conformities	46
14.5 Mechanical data	46
15 Dimensions C60 PVDF	46
15.1 Union end (code 7, 78)	46
15.2 Connection dimensions	46
15.3 Mounting dimensions	48
GEMÜ C60 CleanStar SmartLine	49
16 Availability C60 SmartLine	50
17 Order data C60 SmartLine	51
17.1 Order codes	51
17.2 Order example	51
18 Technical data C60 SmartLine.....	52
18.1 Medium	52
18.2 Temperature	52
18.3 Pressure	52
18.4 Product conformities	53
18.5 Mechanical data	54
19 Dimensions C60 SmartLine	54
19.1 Flare connection (code 75, 77)	54
19.2 Butt weld spigot (code 20).....	55
19.3 Union end (code 78)	56
19.4 Mounting dimensions	57
20 Accessories	58
GEMÜ CFSTF	58
GEMÜ 1098	58
GEMÜ FlareStar	58
GEMÜ TubeStar	58
GEMÜ C67 STA	58

CleanStar product line

				
GEMÜ C60 Clean-Star PFA				
GEMÜ C60 Clean-Star PFA 3/5-way				
GEMÜ C60 Clean-Star PVDF				
GEMÜ C60 Clean-Star SmartLine				
Operation				
Pneumatic	●	●	●	●
Nominal sizes	DN 4 to 50	DN 10 to 15	DN 15	DN 10 to 32
Media temperature	-10 to 150 °C	-10 to 150 °C	-10 to 120 °C	-10 to 80 °C
Connection types				
Butt weld spigot	●	-	-	●
Flare	●	●	-	●
Flare SpaceSaver	●	●	-	-
Nexus Connect® SpaceSaver	●	-	-	-
PrimeLock®	●	-	-	-
PrimeLock® SpaceSaver	●	-	-	-
Super 300 Type Pillar® SpaceSaver	●	-	-	-
Tube spigot	●	-	-	-
Union end	-	-	●	●
Welded-on Nexus Connect®	●	-	-	-
Body materials				
PFA	●	●	-	-
PP-H	-	-	-	●
PP-R	-	-	-	●
PVDF	-	-	●	-
Body configuration				
2/2-way body	●	-	●	●
T-body	●	-	-	-
V valve body	-	●	-	-
Conformities				
EAC	●	●	●	●
FDA	●	●	●	●
TA Luft (German Clean Air Act)	●	●	●	●




Product description






No.	Name	Materials
1	Stroke limiter and optical position indicator	
2	Actuator	PVDF (body)
3	Pneumatic connections	
4	Actuator union nut	PVDF or ECTFE
5	Union nut connections	PVDF, PFA or CPFA
6	Mounting lugs	
7	Leak detection hole	
8	Valve body	PVDF, PFA or PP
	Diaphragm (internal)	PTFE (media wetted) / EPDM

Designs

Body configurations

Body configuration	Description
2/2-way body (code D) 	The 2/2-way body is the most commonly used body configuration. Thanks to the seal created by the weir-style body, the flow direction is freely selectable. Various pipe and tube connections can be connected to the ports, whereby both connections (X and Z) have the same connection size. However, different connection sizes can also be used by attaching corresponding fittings.
T valve body (code T) 	The T body has 3 connections. The opposing connections (X and Z) are classed as main pipe, as media flows between them at all times, regardless of the position (open/closed) of the actuator. The branch (Y) is located at a 90° angle to the main pipe. The flow across this connection can be influenced via the actuator. T valves are often used when regular analyses of the medium are required. To this end, the branch (Y) is opened briefly to remove a small volume of the medium as and when necessary. T valves are often also installed in a ring main, whereby the medium from the ring main is only released via the Y connection when the actuator is in its open position.
V valve (code V) 	The V valve body has 3 connections, two of which (X and Z) can be controlled via valve seats. The following flow schemes can therefore be implemented: <ul style="list-style-type: none"> • Flow between X and Y, as well as between Z and Y (both actuators open) • No flow (both actuators closed) • Flow only between X and Y (one actuator open, one actuator closed) • Flow only between Z and Y (one actuator open, one actuator closed) This diaphragm valve can be configured with two pneumatic and two manual actuators. A combination of both actuator types is also possible. V valves are often used when media need to be mixed at a specific mixing ratio. However, they can also be used to establish redundant media supply or as a mixing valve.

Special versions

	Description
High Flow (code F)  	<p>In actuator sizes 2 and 3, the 2/2-way body is also available in a so-called High Flow design. This body version has a flow-optimized weir geometry. This reduces the pressure loss and thereby facilitates a higher flow. High Flow valve bodies are often used when higher volume flows are required.</p> <p>The upper image shows a cross-section of a standard version without High Flow. The lower image shows a cross-section of a High Flow design (code F).</p>
ECTFE union nut (code E) 	<p>The central union nut, which connects the actuator to the body via a thread, can optionally be ordered in ECTFE. This design is used if the outside environment where the valve is used contains alkaline media. In conditions such as these, a central union nut made from ECTFE can offer improved mechanical and chemical resistance. The materials can be distinguished based on their colour. In comparison with the white PVDF material, ECTFE has a slightly darker colour. The material is also uniquely indicated via an arrow on the union nut.</p>
PFA-coated spring (design 7030) 	<p>When operating in an environment that favours corrosion or otherwise impairs the function of metallic parts, use of a pneumatic valve is unavoidable in certain cases. The PFA coating of the spring can therefore make sense, as it helps maintain functionality.</p>

GEMÜ C60 CleanStar PFA

Pneumatically operated diaphragm valve with PFA valve body



Features

- High purity due to cleanroom manufacturing
- High Flow version selectable
- High flow rate with low-stress media channelling
- Minimal deadleg
- Optional flow direction
- Also available as T valve
- The valve is available with an ECTFE union nut as an option.
- Reduced costs thanks to long service life

Description

The GEMÜ C60 CleanStar® ultra pure 2/2-way diaphragm valve has a plastic piston actuator and is pneumatically operated. A stroke limiter (not with actuator size 4) and an optical position indicator are integrated as standard. All media wetted parts are made of PFA or PTFE. This High Purity version of the CleanStar® series complies with the strictest purity standards and boasts high chemical resistance. It can also be used with high media temperatures. As such, it is often used at the supply and distribution level in semiconductor factories.

Technical specifications

- **Media temperature :** -10 to 150 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 4 to 50
- **Body configurations:** 2/2-way body | T-body
- **Connection types:** Butt weld spigot | Flare | Flare SpaceSaver | Nexus Connect® SpaceSaver | PrimeLock® | PrimeLock® SpaceSaver | Super 300 Type Pillar® SpaceSaver | Tube spigot | Welded-on Nexus Connect®
- **Connection standards:** DIN
- **Body materials:** PFA
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration

Availability C60 PFA

Body configuration - 2/2-way body (code D)

Materials

International code	DN	Connection size X, Z	Connection type (code) ¹⁾			
			30	NX welded	NX SpaceSaver	73, 75, 77, PL, T3
PFA material (code 30)						
4	4	1/4" tube	-	X	-	X
	10	1/4" pipe	X	-	-	-
6	6	3/8" tube	-	X	X	X
8	10	1/2" tube	-	X	X	X
	15	1/2" pipe	X	-	-	-
12	15	3/4" tube	-	X	X	X
	20	3/4" pipe	X	-	-	-
16	20	1" tube	-	X	X	X
	25	1" pipe	X	-	-	-
20	25	1 1/4" tube	-	-	-	X
24	40	1 1/2" pipe	X	-	-	-
32	50	2" pipe	X	-	-	-

1) **Connection type**

Code 30: Spigot – inch, for welding or solvent cementing, depending on the body material

Code 73: Flare connection with CPFA union nut

Code 75: Flare connection with PVDF union nut

Code 77: Flare connection with PFA union nut


Code NX: Nexus Connect connection with PFA union nut

Code PL: PrimeLock connection

Code T3: Tube spigot

Connections

Body configuration - 2/2-way body (code D)



Connection type Flare (code 73, 75, 77)

Actuator size (code)	Connection size (code)	SpaceSaver position			
		None	On one side Pos. X	On one side Pos. Z (code Z)	On both sides Pos. X, Z (code S)
1, 1E	4	X	On request	X	-
	6	X	On request	X	-
2, 2E	8	X	On request	X	X
	12	X	On request	X	X
3, 3E	12	X	On request	X	X
	16	X	On request	X	X
	20	X	On request	X	X

Connection type Flare (code 73, 75, 77) – High Flow design

Actuator size (code)	Connection size (code)	SpaceSaver position			
		None	On one side Pos. X	On one side Pos. Z (code Z)	On both sides Pos. X, Z (code S)
2 F, 2EF	12	X	On request	-	-
2 F, 2EF	16	X	On request	-	-
3 F, 3EF	16	X	On request	-	-
3 F, 3EF	20	X	On request	X	X

Connection type butt weld spigot (code 30)

Actuator size (code)	Connection size X, Z (code)	Butt weld spigot	
		On both sides	On one side, pos. Z
1, 1E	4	X	-
2, 2E	8	X	X
2, 2E	12	X	X
3, 3E	12	X	X
3, 3E	16	X	X
4	24	X	-
4	32	X	-

Connection type butt weld spigot (code 30) - High Flow design

Actuator size (code)	Connection size X, Z (code)	Butt weld spigot	
		On both sides	On one side, pos. Z
2 F	8	X	-
2 F	12	X	-
3 F	16	X	-

Connection type Flare in pos. X, butt weld spigot in pos. Z (code K)

Actuator size (code)	Actuator size (code)	Connection type (code)	
		73, 75, 77	30
		On one side, pos. X	On one side, pos. Z
2, 2E	8	X	X
2, 2E	12	X	X
3, 3E	12	X	X
3, 3E	16	X	X

Connection type Flare in pos. X, butt weld spigot in pos. Z (code K) – High Flow design

Actuator size (code)	Actuator size (code)	Connection type (code)	
		73, 75, 77	30
		On one side, pos. X	On one side, pos. Z
2 F, 2EF	12	X	X
2 F, 2EF	16	X	X
3 F, 3EF	16	X	X

PrimeLock® connection type (code PL)

Actuator size (code)	Connection size (code)	Pos. SpaceSaver	
		Without	
1, 1E	4	X	
	6	X	
2, 2E	8	X	

PrimeLock® (code PL) connection type – High Flow design

Actuator size (code)	Connection size (code)	Pos. SpaceSaver	
		Without	
2 F, 2EF	12	X	
	16	X	
3 F, 3EF	16	X	
	20	X	

Connection type tube spigot (code T3)

Actuator size (code)	Connection size (code)	SpaceSaver position	
		None	
1, 1E	6	X	
2, 2E	8	X	
	12	X	
3, 3E	16	X	

Connection type tube spigot (code T3) – High Flow design


Actuator size (code)	Connection size (code)	SpaceSaver position	
		None	
3 F, 3EF	20	X	

Nexus Connect® connection type (code NX) - Standard (1, 2, 3), High Flow design (2F, 3F)

Actuator size (code)	Connection size	Connection	
		On both sides	
		Welded	SpaceSaver
1	1/4"	X	-

Availability C60 PFA

Actuator size (code)	Connection size	Connection	
		On both sides	
		Welded	SpaceSaver
2	3/8"	X	X
	1/2"	X	X
	3/4"	X	-
2F	3/4"	-	X
3	1"	X	-
3F	1"	-	X

Body configuration - T body (code T)

Connection type Flare (code 73, 75, 77)

Actuator size (code)	Connection size X, Z (code)	Connection size Y (code)	SpaceSaver position				
			None	X	Y	Z	X, Z (code S)
1, 1E	6	4	X	-	-	-	-
	6	6	X	-	-	-	-
	8	6	X	-	-	X	-
	12	6	X	X	-	X	-
2, 2E	8	8	X	X	X	X	X
	12	8	X	X	X	X	X
	12	12	X	X	X	X	-
	16	8	X	X	-	X	X
	16	12	X	X	X	X	-
3, 3E	16	16	X	X	-	X	-
	20	8	X	-	-	X	-
	20	12	X	-	-	X	-
	20	16	X	-	-	X	-
	20	20	X	-	-	X	-

Connection type butt weld spigot (code 30)

Actuator size (code)	Connection size X, Z (code)	Connection size Y (code)	Butt weld spigot, pos. X, Y, Z	Butt weld spigot, pos. X, Z	
				SpaceSaver, pos. Y	Flare connection, pos. Y
1, 1E	4	4	X	-	-
	8	4	X	-	-
2, 2E	8	8	X	X	-
	12	8	X	-	-
	12	8	X	-	X
	12	12	-	-	X
3, 3E	16	8	X	X	X
	16	12	X	-	-
	16	16	X	X	X

Order data C60 PFA

Order data - body configuration - 2/2-way body (code D)

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code
Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)	C60

2 Position of space saver	Code
Without	
Flare connection in position X, butt weld spigot in position Z	K
Space Saver for X+ Z position	S
Space Saver for Z position	Z

3 Connection size	Code
1/4", international code: 4	4
3/8", international code: 6	6
1/2", international code: 8	8
3/4", international code: 12	12
1", international code: 16	16
1 1/4", international code: 20	20
1 1/2", international code: 24	24
2", international code: 32	32

4 Body configuration	Code
2/2-way body	D

5 Connection type	Code
Tube	
Flare connection with CPFA union nut	73
Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77
Nexus Connect connection with PFA union nut	NX
PrimeLock connection	PL
Tube spigot	T3
Pipe	
Spigot – inch, for welding or solvent cementing, depending on the body material	30

6 Valve body material	Code
PFA, perfluoroalkoxy	30

7 Diaphragm material	Code
PTFE/EPDM one-piece	54
PTFE/EPDM two-piece	5M

8 Control function	Code
Normally closed (NC)	1
Normally open (NO)	2

8 Control function	Code
Double acting (DA)	3

9 Actuator version	Code
Standard version	

Actuator size 1	1
Actuator size 2	2
Actuator size 3	3
Actuator size 4	4

Standard version with ECTFE union nut	Code
Actuator size 1, with ECTFE union nut	1E

Actuator size 2, with ECTFE union nut	2E
Actuator size 3, with ECTFE union nut	3E

High Flow design	Code
Actuator size 2 High Flow	2 F
Actuator size 3 High Flow	3 F

High Flow design with ECTFE union nut	Code
Actuator size 2 High Flow, with ECTFE union nut	2EF

Actuator size 3 High Flow, with ECTFE union nut	3EF
--	-----

10 Design	Code
Without	
CleanStar with welded-on NexusConnect fitting	2591
C60, spring PFA coated	7030

11 High Purity version	Code
High purity white	HPW

Order example

Ordering option	Code	Description
1 Type	C60	Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)
2 Position of space saver	Z	Space Saver for Z position
3 Connection size	8	1/2", international code: 8
4 Body configuration	D	2/2-way body
5 Connection type	75	Flare connection with PVDF union nut
6 Valve body material	30	PFA, perfluoroalkoxy
7 Diaphragm material	54	PTFE/EPDM one-piece
8 Control function	1	Normally closed (NC)
9 Actuator version	2	Actuator size 2
10 Design		Without
11 High Purity version	HPW	High purity white

Order data - body configuration - T body (code T)

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code	9 Actuator version	Code
Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)	C60	Actuator size 2, with ECTFE union nut	2E
		Actuator size 3, with ECTFE union nut	3E
2 Position of space saver	Code	10 Position of space saver-2	Code
Without		Space Saver for X position	X
Space Saver for Y position	Y	Space Saver for Z position	Z
		Space Saver for X+ Z position	S
3 Connection size	Code	11 Connection size 2	Code
Position Y		Position X and Z	
1/4", international code: 4	4	1/4", international code-2: 4	4
3/8", international code: 6	6	3/8", international code-2: 6	6
1/2", international code: 8	8	1/2", international code-2: 8	8
3/4", international code: 12	12	3/4", international code-2: 12	12
1", international code: 16	16	1", international code-2: 16	16
1 1/4", international code: 20	20	1 1/4", international code-2: 20	20
4 Body configuration	Code	12 Connection type spigot 2	Code
T-body	T	Tube	
5 Connection type	Code	Spigot – inch, for welding or solvent cementing, depending on the body material	30
Tube		Flare connection with CPFA union nut	73
Flare connection with CPFA union nut	73	Flare connection with PVDF union nut	75
Flare connection with PFA union nut	77	Flare connection with PFA union nut	77
Pipe		Pipe	
Spigot – inch, for welding or solvent cementing, depending on the body material	30	Flare connection with PVDF union nut	75
6 Valve body material	Code	Flare connection with PFA union nut	77
PFA, perfluoroalkoxy	30		
7 Diaphragm material	Code	13 Design	Code
PTFE/EPDM one-piece	54	Without	
		C60, spring PFA coated	7030
8 Control function	Code	14 High Purity version	Code
Normally closed (NC)	1	High purity white	HPW
Normally open (NO)	2		
Double acting (DA)	3		
9 Actuator version	Code		
Standard version			
Actuator size 1	1		
Actuator size 2	2		
Actuator size 3	3		
Standard version with ECTFE union nut			
Actuator size 1, with ECTFE union nut	1E		

Order example

Ordering option	Code	Description
1 Type	C60	Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)
2 Position of space saver	Y	Space Saver for Y position
3 Connection size	8	1/2", international code: 8
4 Body configuration	T	T-body
5 Connection type	75	Flare connection with PVDF union nut
6 Valve body material	30	PFA, perfluoroalkoxy
7 Diaphragm material	54	PTFE/EPDM one-piece
8 Control function	1	Normally closed (NC)
9 Actuator version	2	Actuator size 2
10 Position of space saver-2	Z	Space Saver for Z position
11 Connection size 2	8	1/2", international code-2: 8
12 Connection type spigot 2	75	Flare connection with PVDF union nut
13 Design		Without
14 High Purity version	HPW	High purity white

Technical data C60 PFA

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: PFA valve body material (code 30): -10 – 150 °C
Observe pressure/temperature diagram

Ambient temperature: 0 – 60 °C


Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar

Pressure/temperature diagram:

Valve body material PFA (code 30)



Note: The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation.
Temperatures below 0 °C can have a negative influence on the actuation speed.

Cv values:

Body configuration - 2/2-way body (code D)

Actuator size (code)	Connection size	Connection	
		On both sides	
	X, Z	Tube connection	Pipe connection
1, 1E	1/4"	4.0	15.0
	3/8"	15.0	-
2, 2E	1/2"	35.0	68.0
	3/4"	68.0	68.0
3, 3E	3/4"	68.0	126.0
	1"	158.0	175.0
	1 1/4"	170.0	-
4	1 1/2 "	-	1225.0
	2"	-	1225.0

Kv values in l/min

If the 2/2-way body has a tube and pipe connection, the Kv values of the tube connection are used.

Cv values:**Body configuration - 2/2-way body (code D) – High Flow design**

Actuator size (code)	Connection size	Connection	
		On both sides	
	X, Z	Tube connection	Pipe connection
2 F, 2EF	1/2"	-	115.0
	3/4"	115.0	115.0
	1"	123.0	123.0
3 F, 3EF	1"	316.0	316.0
	1¼"	325.0	-

Kv values in l/min

Body configuration – 2/2-way body (code D) – Nexus Connect® connection type (code NX)

Actuator size (code)	Connection size	Connection	
		On both sides	
	X, Z	Welded	SpaceSaver
1	1/4"	7.82	-
	3/8"	13.0	13.3
2	1/2"	48.1	35.2
	3/4"	66.3	-
2F	3/4"	-	110.0
3	1"	142.0	-
3F	1"	-	255.0

Kv values in l/min

Cv values:**Body configuration - T body (code T)**

Actuator size (code)	Connection size		Connection		
			On both sides at main pipe (X, Z) and branch (Y)		One side
	Main pipe X, Z	Branch Y	Tube connec- tion	Pipe connec- tion	Pipe/tube con- nection
1, 1E	1/4"	1/4"	-	17.0	-
	3/8"	1/4"	4.0	-	-
	3/8"	3/8"	13.0	-	-
	1/2"	1/4"	-	18.0	-
	1/2"	3/8"	17.0	-	-
	3/4"	3/8"	18.0	-	-
2, 2E	1/2"	1/2"	28.0	62.0	36.0
	3/4"	1/4"	-	35.0	-
	3/4"	1/2"	35.0	38.0	38.0
	3/4"	3/4"	62.0	71.0	-
	1"	1/2"	38.0	101.0	-
	1"	3/4"	71.0	-	-
3, 3E	1"	1"	137.0	135.0	145.0
	1"	1/2"	-	101.0	42.0
	1"	3/4"	-	130.0	-
	1 1/4"	1/2"	53.0	-	-
	1 1/4"	3/4"	117.0	-	-
	1 1/4"	1"	150.0	-	-
	1 1/4"	1 1/4"	170.0	-	-

At branch Y

Kv values in l/min

Vacuum:



400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.

Pneumatic actuator**Control pressure:**

Control function	Actuator size	Control pressure
1	1, 1E	5.5 - 7 bar
	2, 2E, 2 F, 2EF	4 - 7 bar
	3, 3E, 3 F, 3EF	5 - 7 bar
	4	5 - 7 bar
2, 3	1, 1E; 2, 2E, 2 F, 2EF; 3, 3E, 3 F, 3EF	max. 4 bar
	4	max. 4.5 bar

Control pressure / operating pressure characteristics:

Control function 1 - normally closed (NC)**Control function 2 - normally open (NO)****Control air connection:**

G 1/8

Filling volume:

Actuator size	Control function			
	Normally closed (NC)	Normally open (NO)	Double acting (closed) (DA)	Double acting (open) (DA)
1, 1E	7.4	9.2	9.2	7.4
2, 2E, 2 F, 2EF	24.0	39.0	39.0	24.0
3, 3E, 3 F, 3EF	56.0	88.0	88.0	56.0
4	146.0	794.0	146.0	956.0

Filling volume in cm³

Product conformities

Machinery Directive: 2006/42/EC

Food: FDA

EAC: The product is certified according to EAC.


Mechanical data

Flow direction: Optional

Dimensions C60 PFA

2/2-way valves (code D)

Flare connection (code 73, 75, 77)



Actuator size ¹⁾	Connection size	Space saver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
1, 1E	1/4"	-	51.4	38.0	107.0	13.6	112.8	56.4	56.4
1, 1E	1/4"	Z	51.4	38.0	107.0	13.6	120.1	56.4	63.7
1, 1E	3/8"	-	51.4	38.0	107.0	13.6	114.0	57.0	57.0
1, 1E	3/8"	Z	51.4	38.0	107.0	13.6	119.4	57.0	62.4
2, 2E	1/2"	K	64.0	64.7	126.5	19.0	133.4	65.9	67.5
2, 2E	1/2"	-	64.0	64.7	120.5	16.0	131.8	65.9	65.9
2, 2E	1/2"	S	64.0	64.7	120.5	16.0	142.0	71.0	71.0
2, 2E	1/2"	Z	64.0	64.7	120.5	16.0	136.9	65.9	71.0
2, 2E	3/4"	K	64.0	64.7	126.5	19.0	134.4	66.9	67.5
2, 2E	3/4"	-	64.0	64.7	126.5	19.0	133.8	66.9	66.9
3, 3E	3/4"	K	80.0	86.0	165.9	25.0	165.8	82.9	82.9
2, 2E	3/4"	S	64.0	64.7	126.5	19.0	156.8	78.4	78.4
2, 2E	3/4"	Z	64.0	64.7	126.5	19.0	145.3	66.9	78.4
3, 3E	3/4"	-	80.0	86.0	165.8	25.0	165.8	82.9	82.9
3, 3E	1"	K	80.0	86.0	172.5	25.0	172.5	89.5	83.0
3, 3E	1"	-	80.0	86.0	179.0	25.0	179.0	89.5	89.5
3, 3E	1"	S	80.0	86.0	198.8	25.0	198.8	99.4	99.4
3, 3E	1"	Z	80.0	86.0	188.9	25.0	188.9	89.5	99.4
3, 3E	1 1/4"	-	80.0	86.0	238.4	25.0	238.4	119.2	119.2
2 F, 2EF	3/4"	-	64.0	64.7	126.5	19.0	133.8	66.9	66.9
2 F, 2EF	3/4"	S	64.0	64.7	126.5	19.0	156.8	78.4	78.4
2 F, 2EF	3/4"	Z	64.0	64.7	126.5	19.0	145.3	66.9	78.4
2 F, 2EF	1"	-	64.0	64.7	126.5	19.0	160.0	80.0	80.0

Dimensions C60 PFA

Actuator size ¹⁾	Connection size	Space saver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
3 F, 3EF	1"	-	80.0	86.0	179.0	25.0	179.0	89.5	89.5
3 F, 3EF	1"	S	80.0	86.0	198.8	25.0	198.8	99.4	99.4
3 F, 3EF	1"	Z	80.0	86.0	188.9	25.0	188.9	89.5	99.4
3 F, 3EF	1¼"	-	80.0	86.0	197.4	25.0	238.4	119.2	119.2

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut


2) Position of space saver

Code K: Flare connection in position X, butt weld spigot in position Z

Code S: Space Saver for X+ Z position

Code Z: Space Saver for Z position

Butt weld spigot (code 30)



Actuator size ¹⁾	Connec-tion size	Space saver po-sition ²⁾	ØB	ØB1	H	H1	L	L1	L2	Spigot (A)	
										Ød	Ød1
1, 1E	1/4"	-	51.4	38.0	107.0	13.6	102.0	51.0	51.0	13.7	9.2
2, 2E	1/2"	-	64.0	64.7	126.5	19.0	135.0	67.5	67.5	21.3	15.8
2, 2E	3/4"	-	64.0	64.7	126.5	19.0	135.0	67.5	67.5	26.7	20.3
3, 3E	3/4"	-	80.0	82.9	166.0	25.0	166.0	83.0	83.0	26.7	20.3
3, 3E	1"	-	80.0	83.0	166.0	25.0	166.0	83.0	83.0	33.4	26.6
4	1½"	-	132.3	153.0	349.6	40.0	194.0	97.0	97.0	48.3	40.9
4	2"	-	132.3	153.0	349.6	40.0	224.0	112.0	112.0	60.3	52.3
High Flow											
2 F, 2EF	1/2"	-	64.0	64.7	126.5	19.0	135.0	67.5	67.5	21.3	15.8
2 F, 2EF	3/4"	-	64.0	64.7	126.5	19.0	135.0	67.5	67.5	26.7	20.3
2 F, 2EF	1"	-	64.0	64.7	126.5	19.0	148.0	74.0	74.0	33.4	26.6
3 F, 3EF	1"	-	80.0	83.0	166.0	25.0	166.0	83.0	83.0	33.4	26.6

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut


Code 4: Actuator size 4

2) Position of space saver

Code K: Flare connection in position X, butt weld spigot in position Z

Code S: Space Saver for X+ Z position

Code Z: Space Saver for Z position

PrimeLock® connection (code PL)

Actuator size ¹⁾	Connection size	Space saver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
1, 1E	1/4"	-	51.4	38.0	107.0	15.0	113.0	57.0	57.0
1, 1E	3/8"	-	51.4	38.0	107.0	15.0	117.0	59.0	59.0
2, 2E	1/2"	-	64.0	64.7	126.5	16.0	141.0	71.0	71.0
2 F, 2EF	3/4"	-	64.0	64.7	126.5	19.0	156.0	79.0	79.0
2 F, 2EF	1"	-	64.0	64.7	126.5	19.0	169.0	85.0	85.0
3 F, 3EF	1"	-	80.0	86.0	185.0	25.0	150.5	94.0	94.0
3 F, 3EF	1¼"	-	80.0	86.0	209.0	25.0	150.5	105.0	105.0

Dimensions in mm

1) **Actuator version**

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut


Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) **Position of space saver**

Code K: Flare connection in position X, butt weld spigot in position Z

Code S: Space Saver for X+Z position

Code Z: Space Saver for Z position

Tube spigot (code T3)

Actuator size ¹⁾	Connec-tion size	Space saver po-sition ²⁾	ØB	ØB1	H	H1	L	L1	L2	Spigot (A)	
										Ød	Ød1
1, 1E	3/8"	-	51.4	38.0	107.0	13.6	106.0	53.0	53.0	9.5	6.6
2, 2E	1/2"	-	64.0	64.7	120.5	16.0	122.0	61.0	61.0	12.7	9.7
2, 2E	3/4"	-	64.0	64.7	126.5	19.0	135.0	67.5	67.5	19.05	15.9
3, 3E	1"	-	80.0	86.0	165.8	150.5	25.0	82.5	82.5	25.4	22.2
2 F, 2EF	3/4"	-	64.0	64.7	126.5	19.0	135.0	67.5	67.5	19.05	15.9
2 F, 2EF	1"	-	64.0	64.7	126.5	19.0	148.0	74.0	74.0	25.4	22.2
3 F, 3EF	1"	-	80.0	86.0	165.0	150.5	25.0	82.5	82.5	25.4	22.2
3 F, 3EF	1 1/4"	-	80.0	86.0	176.0	150.5	25.0	88.0	88.0	31.75	28.2

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut


Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) Position of space saver

Code K: Flare connection in position X, butt weld spigot in position Z

Code S: Space Saver for X+ Z position

Code Z: Space Saver for Z position

Nexus Connect® (code NX)**Nexus Connect®, welded**

Actuator size ¹⁾	Connection size	Space saver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
1	1/4"	-	51.4	38.0	107.0	13.6	140.5	70.3	70.3
1	3/8"	-	51.4	38.0	107.0	13.6	147.7	73.9	73.9
2	1/2"	-	64.0	64.7	126.5	19.0	153.0	76.5	76.5
2	3/4"	-	64.0	64.7	126.5	19.0	179.1	89.6	89.6
3	1"	-	80.0	86.0	166.5	25.0	205.0	102.5	102.5

Nexus Connect® SpaceSaver

Actuator size ¹⁾	Connection size	Space saver position ²⁾	ØB	ØB1	H	H1	L	L1	L2
1	3/8"	X, Z	51.4	38.0	107.0	13.6	112.4	56.2	56.2
2	1/2"	X, Z	64.0	64.7	120.4	16.0	131.6	65.8	65.8
2F	3/4"	X, Z	64.0	64.7	126.5	19.0	145.1	72.6	72.6
3F	1"	X, Z	80.0	86.0	166.5	25.0	176.3	88.2	88.2


Dimensions in mm

1) Actuator version

- Code 1: Actuator size 1
- Code 2: Actuator size 2
- Code 2 F: Actuator size 2 High Flow
- Code 3: Actuator size 3
- Code 3 F: Actuator size 3 High Flow

2) Position of space saver

- Code X: Space Saver for X position
- Code Z: Space Saver for Z position

T body (code T)**Flare connection (code 73, 75, 77)**

Actuator size ¹⁾	Connection size		Space saver position ²⁾		ØB	ØB1	H	H1	H2	L	L1	L2	L3	L4
	Pos. (X, Z)	Pos. (Y)	Pos. (X, Z)	Pos. (Y)										
1, 1E	3/8"	1/4"	-	-	51.4	38.0	114.5	19.0	23.0	115.0	57.5	57.5	67.4	84.4
1, 1E	3/8"	3/8"	-	-	51.4	38.0	114.5	19.0	23.0	115.0	57.5	57.5	68.0	85.0
1, 1E	1/2"	3/8"	-	-	51.4	38.0	114.5	19.0	23.0	120.8	60.4	60.4	68.0	85.0
1, 1E	1/2"	3/8"	Z	-	51.4	38.0	114.5	19.0	23.0	131.9	60.4	71.5	68.0	85.0
1, 1E	3/4"	3/8"	-	-	51.4	38.0	114.5	19.0	23.0	125.8	62.9	62.9	68.0	85.0
1, 1E	3/4"	3/8"	X	-	51.4	38.0	114.5	19.0	23.0	135.3	72.4	62.9	68.0	85.0
1, 1E	3/4"	3/8"	Z	-	51.4	38.0	114.5	19.0	23.0	135.3	62.9	72.4	68.0	85.0
2, 2E	1/2"	1/2"	-	-	64.0	64.7	126.5	19.0	19.0	131.8	65.9	65.9	80.4	98.4
2, 2E	1/2"	1/2"	Z	-	64.0	64.7	126.5	19.0	19.0	136.0	65.9	70.1	80.4	98.4
2, 2E	1/2"	1/2"	-	Y	64.0	64.7	126.5	19.0	19.0	131.8	65.9	65.9	85.5	103.5
2, 2E	3/4"	1/2"	-	-	64.0	64.7	126.5	19.0	19.0	133.8	66.9	66.9	80.4	98.4
2, 2E	3/4"	1/2"	S	-	64.0	64.7	126.5	19.0	19.0	156.8	78.4	78.4	80.4	98.4
2, 2E	3/4"	1/2"	X	-	64.0	64.7	126.5	19.0	19.0	145.3	78.4	66.9	80.4	98.4
2, 2E	3/4"	1/2"	Z	-	64.0	64.7	126.5	19.0	19.0	145.3	66.9	78.4	80.4	98.4
2, 2E	3/4"	1/2"	-	Y	64.0	64.7	126.5	19.0	19.0	133.8	66.9	66.9	85.5	103.5
2, 2E	3/4"	3/4"	-	-	64.0	64.7	126.5	19.0	19.0	133.8	66.9	66.9	81.4	99.4
2, 2E	3/4"	3/4"	X	-	64.0	64.7	126.5	19.0	19.0	145.3	78.4	66.9	81.4	99.4
2, 2E	3/4"	3/4"	Z	-	64.0	64.7	126.5	19.0	19.0	145.3	66.9	78.4	81.4	99.4
2, 2E	3/4"	3/4"	-	Y	64.0	64.7	126.5	19.0	19.0	133.8	66.9	66.9	92.4	110.4
3, 3E	1"	1"	-	-	80.0	86.0	166.5	25.0	25.0	168.0	84.0	84.0	110.5	133.0
3, 3E	1"	1"	X	-	80.0	86.0	166.5	25.0	25.0	177.9	93.9	84.0	110.5	133.0
3, 3E	1"	1"	Z	-	80.0	86.0	166.5	25.0	25.0	177.9	84.0	93.9	110.5	133.0
3, 3E	1 1/4"	1/2"	-	-	80.0	86.0	166.5	25.0	25.0	238.4	119.2	119.2	99.9	122.4
3, 3E	1 1/4"	1"	-	-	80.0	86.0	166.5	25.0	25.0	238.4	119.2	119.2	110.5	133.0

Dimensions C60 PFA

Actuator size ¹⁾	Connection size		Space saver position ²⁾		ØB	ØB1	H	H1	H2	L	L1	L2	L3	L4
	Pos. (X, Z)	Pos. (Y)	Pos. (X, Z)	Pos. (Y)										
3, 3E	1 1/4"	1 1/4"	-	-	80.0	86.0	166.5	25.0	25.0	238.4	119.2	119.2	143.2	165.7
2 F, 2EF	1"	1/2"	-	-	64.0	64.7	135.9	25.0	28.5	154.0	77.0	77.0	81.4	100.9
2 F, 2EF	1"	1/2"	S	-	64.0	64.7	135.9	25.0	28.5	163.8	81.9	81.9	81.4	100.9
2 F, 2EF	1"	1/2"	X	-	64.0	64.7	135.9	25.0	28.5	158.9	81.9	77.0	81.4	100.9
2 F, 2EF	1"	1/2"	Z	-	64.0	64.7	135.9	25.0	28.5	158.9	77.0	81.9	81.4	100.9
2 F, 2EF	1"	3/4"	-	-	64.0	64.7	135.9	25.0	28.5	154.0	77.0	77.0	82.4	101.9
2 F, 2EF	1"	3/4"	X	-	64.0	64.7	135.9	25.0	28.5	158.9	81.9	77.0	82.4	101.9
2 F, 2EF	1"	3/4"	Z	-	64.0	64.7	135.9	25.0	28.5	158.9	77.0	81.9	82.4	101.9
2 F, 2EF	1"	3/4"	-	Y	64.0	64.7	135.9	19.0	28.5	154.0	77.0	77.0	92.9	112.4

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut


Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) Position of space saver

Code X: Space Saver for X position

Code Y: Space Saver for Y position

Code Z: Space Saver for Z position

Butt weld spigot (code 30)

Dimensions Spigot (A) (see "Butt weld spigot (code 30)", page 25)

Actuator size ¹⁾	Connection size		Space saver connection position ²⁾	ØB	ØB1	H	H1	H2	L	L1	L2	L3	L4	
	Pos. (X, Z)	Pos. (Y)												
1, 1E	1/4"	1/4"	-	73, 75, 77	51.4	38.0	114.5	19.0	23.0	106.0	53.0	53.0	63.5	80.5
1, 1E	1/4"	1/2"	-	30	51.4	38.0	114.5	19.0	23.0	106.0	53.0	53.0	63.5	80.5
2, 2E	1/2"	1/2"	-	30	64.0	64.7	126.5	19.0	19.0	122.0	61.0	61.0	75.54	93.5
2, 2E	1/4"	3/4"	-	30	64.0	64.7	135.9	25.0	28.5	140.0	70.0	70.0	76.5	96.0
3, 3E	1/2"	1"	-	30	80.0	86.0	166.5	25.0	25.0	163.0	81.5	81.5	102.0	124.5
3, 3E	1/2"	1"	-	73, 75, 77	80.0	86.0	166.5	25.0	25.0	163.0	81.5	81.5	99.9	122.4
3, 3E	3/4"	1"	-	30	80.0	86.0	166.5	25.0	25.0	163.0	81.5	81.5	102.0	124.5
3, 3E	1"	1"	-	30	80.0	86.0	166.5	25.0	25.0	163.0	81.5	81.5	103.5	126.0

Dimensions C60 PFA

Actuator size ¹⁾	Connection size		Space saver position ²⁾	Con-nection ³⁾	ØB	ØB1	H	H1	H2	L	L1	L2	L3	L4
	Pos. (X, Z)	Pos. (Y)												
3, 3E	1"	1"	-	73, 75, 77	80.0	86.0	166.5	25.0	25.0	163.0	81.5	81.5	110.5	133.0

Dimensions in mm

1) Actuator version

Code 1: Actuator size 1

Code 1E: Actuator size 1, with ECTFE union nut

Code 2: Actuator size 2

Code 2 F: Actuator size 2 High Flow

Code 2E: Actuator size 2, with ECTFE union nut

Code 2EF: Actuator size 2 High Flow, with ECTFE union nut

Code 3: Actuator size 3

Code 3 F: Actuator size 3 High Flow

Code 3E: Actuator size 3, with ECTFE union nut

Code 3EF: Actuator size 3 High Flow, with ECTFE union nut

2) Position of space saver

Code X: Space Saver for X position

Code Y: Space Saver for Y position

Code Z: Space Saver for Z position

3) Connection type

Code 30: Spigot – inch, for welding or solvent cementing, depending on the body material


Code 73: Flare connection with CPFA union nut

Code 75: Flare connection with PVDF union nut


Code 77: Flare connection with PFA union nut

Mounting dimensions

2/2-way valve (code D)



T valve (code T)



2/2-way valves (code D)

Actuator size	ϕd	A	B	C
1, 1E	5.5	50.5	25.25	33.5
2, 2E, 2 F, 2EF	5.5	61.5	31.0	40.0
3, 3E, 3 F, 3EF	6.5	78.0	39.0	56.0
4	9.0	124.0	62.0	94.0


Dimensions in mm

T valve (code T)

Actuator size	ϕd	A	B	C
1, 1E	5.5	44.3	27.3	50.0
2, 2E, 2 F, 2EF	5.5	61.5	43.5	41.5
3, 3E, 3 F, 3EF	6.5	79.5	57.0	52.5

Dimensions in mm

Mounting holes, round and slotted hole



Dimensions in mm

Dear customers,

In order to simplify installation, we are switching over the mounting holes to slotted holes for all valve sizes.

Due to the gradual changeover in manufacturing, you may therefore receive valve bodies with new slotted holes and also with the old, round boreholes during this phase.

We ask for your understanding in this matter.

GEMÜ C60 CleanStar PFA 3/5-way

Pneumatically operated 3/5-way diaphragm valve with PFA valve body



Features

- High flow rate
- Minimal contamination
- Minimal deadleg
- Optional flow direction
- Can be used as a media mixing configuration or manifold valve
- Both actuators can be independently controlled
- Combination of manual and pneumatic actuator selectable

Description

The ultra pure GEMÜ C60 CleanStar® 3/5-way diaphragm valve with a V valve body made of PFA has two valve seats. All media wetted parts are made of PFA or PTFE (diaphragm). The external actuator parts are made of PVDF. Solid mounting lugs, as well as a leak detection hole are integrated as standard. The union nuts are available in PVDF, PFA and C-PFA. This High Purity version of the CleanStar® series complies with the strictest purity standards and boasts high chemical resistance. It can also be used with high media temperatures. As such, it is often used at the supply and distribution level in semiconductor factories, particularly to collect or mix media flows.

Technical specifications

- **Media temperature :** -10 to 150 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 10 to 15
- **Body configurations:** V valve body
- **Connection types:** Flare | Flare SpaceSaver
- **Connection standards:** DIN
- **Body materials:** PFA
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)


Technical data depends on the respective configuration

Availability C60 PFA 3/5-way

Connections

Actuator size	Flare connection	SpaceSaver position					Butt weld spigot
		Connection size X, Y, Z	None	X (code X)	Y (code Y)	Z (code Z)	
			Code				
2	8	X	On request				
	12	X	On request				

Actuator assignments



V1		V2		Control function (code)	
Valve 1 (position X - Y)		Valve 2 (position Z - Y)			
Type	Control function	Type	Control function		
C60	Normally closed (NC)	C60	Normally closed (NC)	1	
C60	Normally closed (NC)	C60	Normally open (NO)	D	
C60	Normally closed (NC)	C67	Manually operated	F	
C60	Normally open (NO)	C60	Normally open (NO)	2	
C60	Normally open (NO)	C60	Normally closed (NC)	G	
C60	Normally open (NO)	C67	Manually operated	K	
C60	Normally open (NO)	C60	Double acting	H	
C67	Manually operated	C60	Normally closed (NC)	A	
C67	Manually operated	C60	Normally open (NO)	B	
C67	Manually operated	C67	Manually operated	0	

Order data C60 PFA 3/5-way

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

Provisionally only designs with the same nominal sizes in all positions

1 Type	Code	8 Control function	Code
C60 - valve 1 (between X - Y)		Normally open, double acting	H
Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)	C60	C60 / C67	
C67 - valve 1 (between X - Y)		Normally closed, manually operated	F
Diaphragm valve, manually operated, plastic handwheel, seal adjuster	C67	Normally open, manually operated	K
2 Position of space saver	Code	C67 / C60	
Without		Manually operated, normally closed	A
Space Saver for X+ Z position	S	C67 / C67	
Space Saver for X position	X	Manually operated	0
Space Saver for Y position	Y	3	
Space Saver for Z position	Z	Standard version	
3 Connection size	Code	Standard version with ECTFE union nut	
Position Y		Actuator size 2	2
1/2", international code: 8	8	Actuator size 2, with ECTFE union nut	2E
3/4", international code: 12	12	4	
4 Body configuration	Code	10 Design	Code
Multi-port body V-form	V	Without	
5 Connection type	Code	C60, spring PFA coated	7030
Tube		11 Position of space saver-2	Code
Flare connection with CPFA union nut	73	Without	
Flare connection with PVDF union nut	75	Space Saver for X+ Z position	S
Flare connection with PFA union nut	77	Space Saver for X position	X
6 Valve body material	Code	Space Saver for Y position	Y
PFA, perfluoroalkoxy	30	Space Saver for Z position	Z
7 Diaphragm material	Code	12 Connection size 2	Code
PTFE/EPDM one-piece	54	Position X and Z	
8 Control function	Code	1/2", international code-2: 8	8
C60 / C60		3/4", international code-2: 12	12
Normally closed (NC)	1	13 Connection type spigot 2	Code
Normally open (NO)	2	Position X and Z	
Normally closed, normally open	D	Tube	
Normally open, normally closed	G	Flare connection with CPFA union nut	73
		Flare connection with PVDF union nut	75
		Flare connection with PFA union nut	77
		14 High Purity version	Code
		High purity white	HPW

Order example

Ordering option	Code	Description
1 Type	C60	Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)
2 Position of space saver	Y	Space Saver for Y position
3 Connection size	8	1/2", international code: 8
4 Body configuration	V	Multi-port body V-form
5 Connection type	75	Flare connection with PVDF union nut
6 Valve body material	30	PFA, perfluoroalkoxy
7 Diaphragm material	54	PTFE/EPDM one-piece
8 Control function	F	Normally closed, manually operated
9 Actuator version	2	Actuator size 2
10 Design		Without
11 Position of space saver-2	S	Space Saver for X+ Z position
12 Connection size 2	8	1/2", international code-2: 8
13 Connection type	75	Flare connection with PVDF union nut
14 High Purity version	HPW	High purity white

Technical data C60 PFA 3/5-way

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: PFA valve body material (code 30): -10 – 150 °C
Observe pressure/temperature diagram

Ambient temperature: 0 – 60 °C


Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar

Pressure/temperature diagram:

Valve body material PFA (code 30)



Note: The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation.
Temperatures below 0 °C can have a negative influence on the actuation speed.

Cv values:

Actuator size	Body configuration	Connection size	Connection
		X, Y, Z	Tube
2	V	1/2"	28.0
		3/4"	53.0

Kv values in l/min

If the 2/2-way body has a tube and pipe connection, the Kv values of the tube connection are used.



Vacuum:

400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.

Pneumatic actuator**Control pressure:**

Control function	Actuator size	Control pressure
1	2	4 - 7 bar
2, 3	2	max. 4 bar

Control pressure / operating pressure characteristics:**Control function 1 - normally closed (NC)****Control function 2 - normally open (NO)****Control air connection:**

G 1/8

Filling volume:

Actuator size	Control function			
	Normally closed (NC)	Normally open (NO)	Double acting (closed) (DA)	Double acting (open) (DA)
2	24.0	39.0	39.0	24.0

Filling volume in cm³

Product conformities

Machinery Directive: 2006/42/EC


Food: FDA

EAC: The product is certified according to EAC.

Mechanical data

Flow direction: Optional

Dimensions C60 PFA 3/5-way



Dimensions in mm/inch

GEMÜ C60 CleanStar PVDF

Pneumatically operated diaphragm valve with PVDF valve body



Features

- Ideal for high purity media (for example ultra pure water)
- High flow rate
- Minimal deadleg
- Optional flow direction
- Manufactured in cleanroom conditions
- Union end for easy radial installation and removal reduces maintenance costs

Description

The GEMÜ C60 CleanStar® ultra pure 2/2-way diaphragm valve has a plastic piston actuator and is pneumatically operated. A stroke limiter and an optical position indicator are integrated as standard. All media wetted parts are made of PFA or PTFE. This High Purity version of the CleanStar® series complies with strict purity standards and boasts excellent chemical resistance. These valves are therefore often used in the ultra pure water industry.

Technical specifications

- **Media temperature :** -10 to 120 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal size:** DN 15
- **Body configurations:** 2/2-way body
- **Connection types:** Union end
- **Connection standards:** DIN
- **Body materials:** PVDF
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration

Availability Cleanstar C60 PVDF

Actuator size	DN	Union end (code 7, 78)	Code
2	15	X	15

Order data C60 PVDF

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code	5 Valve body material	Code
Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter	C60	PVDF	20
2 DN	Code	6 Diaphragm material	Code
DN 15	15	PTFE/EPDM one-piece	54
3 Body configuration	Code	7 Control function	Code
2/2-way body	D	Normally closed (NC)	1
4 Connection type	Code	Normally open (NO)	2
Union end with insert (socket) – DIN	7	Double acting (DA)	3
Union end with insert (for IR butt welding) – DIN	78		
		8 Actuator version	Code
		Actuator size 2	2
		9 High Purity version	Code
		Without	
		High Purity white	HPW

Order example

Ordering option	Code	Description
1 Type	C60	Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter
2 DN	15	DN 15
3 Body configuration	D	2/2-way body
4 Connection type	78	Union end with insert (for IR butt welding) – DIN
5 Valve body material	20	PVDF
6 Diaphragm material	54	PTFE/EPDM one-piece
7 Control function	1	Normally closed (NC)
8 Actuator version	2	Actuator size 2
9 High Purity version	HPW	High Purity white

Technical data C60 PVDF

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: Valve body material PVDF (code 20): -10 – 120 °C

Observe pressure/temperature diagram


Ambient temperature: 0 – 60 °C

Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar

Pressure/temperature diagram:



Note: The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation. Temperatures below 0 °C can have a negative influence on the actuation speed.

Cv values:

Actuator size	DN	Connection size		Connection
		Pipe	Union end	
2	15	1/2"	68.0	

Kv values in l/min



Vacuum:

400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.

Pneumatic actuator**Control pressure:**

Control function	Actuator size	Control pressure
1	2	4 - 7 bar
2, 3	2	max. 4 bar

Control pressure / operating pressure characteristics:**Control function 1 - normally closed (NC)****Control function 2 - normally open (NO)****Control air connection:**

G 1/8

Filling volume:

Actuator size	Control function			
	Normally closed (NC)	Normally open (NO)	Double acting (closed) (DA)	Double acting (open) (DA)
2	24.0	39.0	39.0	24.0

Filling volume in cm³

Product conformities

Machinery Directive: 2006/42/EC

Food: FDA


EAC: The product is certified according to EAC.

Mechanical data

Flow direction: Optional

Dimensions C60 PVDF

Union end (code 7, 78)




Actuator size	DN	B	H	L	L1	L2
2	15	65.0	132.0		see connection dimensions	


Dimensions in mm

Connection dimensions

Union end (code 7)




Dimensions in mm

Union end (code 78)

Dimensions in mm

Mounting dimensions

2/2-way valve (code D)




2/2-way valves (code D)

Actuator size	$\varnothing d$	A	B	C
2, 2E, 2 F, 2EF	5.5	61.5	31.0	40.0

Dimensions in mm

Mounting holes, round and slotted hole



Dimensions in mm

Dear customers,

In order to simplify installation, we are switching over the mounting holes to slotted holes for all valve sizes.

Due to the gradual changeover in manufacturing, you may therefore receive valve bodies with new slotted holes and also with the old, round boreholes during this phase.

We ask for your understanding in this matter.

GEMÜ C60 CleanStar SmartLine

SmartLine pneumatically operated diaphragm valve with PP body



Features

- Improved flow capability over PFA versions
- Affordable CleanStar type for applications with less strict requirements in terms of purity
- PTFE diaphragm
- Choice of valve bodies made of PP-R natural or PP-H grey
- Manufactured in a monitored atmosphere

Description

This GEMÜ C60 CleanStar® 2/2-way diaphragm valve has a valve body made of PP and is therefore an affordable alternative to the ultra pure designs. It has been specifically developed for industrial applications with less strict purity requirements (for example solar energy industry). All media wetted parts are made of PP or PTFE (diaphragm). The exterior actuator parts are produced from PVDF. A stroke limiter and an optical position indicator are integrated as standard. A leakage sensor connection is provided.

Technical specifications

- **Media temperature :** -10 to 80 °C
- **Ambient temperature:** 0 to 60 °C
- **Operating pressure :** 0 to 6 bar
- **Nominal sizes:** DN 10 to 32
- **Body configurations:** 2/2-way body
- **Connection types:** Butt weld spigot | Flare | Union end
- **Connection standards:** DIN
- **Body materials:** PP-H, grey | PP-H, natural
- **Diaphragm materials:** PTFE/EPDM
- **Conformities:** EAC | FDA | TA Luft (German Clean Air Act)

Technical data depends on the respective configuration

Availability C60 SmartLine

Actuator size	DN	Flare connection	Butt weld spigot		Union end	Code
			Connection size X, Z	Connection size Z		
2	10	1/2" - 1/2"	-	On request	-	8
	15	-	15 - 15	On request	-	15
	15	3/4" - 3/4"	-	On request	-	12
	20	-	20 - 20	On request	-	20
	20	1" - 1"	-	On request	-	16
	25	-	25 - 25	On request	-	25
3	20	-	20 - 20	On request	-	20
	25	1" - 1"	-	On request	-	16
	25	-	25 - 25	On request	-	25
	25	-	-	On request	25 - 25	25
	25	1 1/4" - 1 1/4"	-	On request	-	20
	32	-	32 - 32	On request	-	32

Order data C60 SmartLine

Order codes

The order data provide an overview of standard configurations.

Please check the availability before ordering. Other configurations available on request.

1 Type	Code	4 Connection type	Code
Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)	C60	Flare connection with PFA union nut	77
		Union end with DIN insert (for IR butt welding)	78
2 Connection size	Code	5 Valve body material	Code
1/2", international code: 8	8	PP-H, grey	G5
DN 15	15	PP-R, natural	R5
3/4", international code: 12	12		
DN 20	20		
1", international code: 16	16		
DN 25	25		
1 1/4", international code: 20	20		
DN 32	32		
3 Body configuration	Code	6 Diaphragm material	Code
2/2-way body	D	PTFE/EPDM one-piece	54
4 Connection type	Code	7 Control function	Code
Spigot for IR butt welding	20	Normally closed (NC)	1
Flare connection with PVDF union nut	75	Normally open (NO)	2
		Double acting (DA)	3
8 Actuator version	Code	9 High Purity version	Code
Actuator size 2	2	Without	
Actuator size 3	3	Smart Line	HPS

Order example

Ordering option	Code	Description
1 Type	C60	Diaphragm valve, pneumatically operated, plastic piston actuator, optical position indicator, stroke limiter (for actuator size 1–3 only)
2 Connection size	8	1/2", international code: 8
3 Body configuration	D	2/2-way body
4 Connection type	78	Union end with DIN insert (for IR butt welding)
5 Valve body material	G5	PP-H, grey
6 Diaphragm material	54	PTFE/EPDM one-piece
7 Control function	1	Normally closed (NC)
8 Actuator version	2	Actuator size 2
9 High Purity version	HPS	Smart Line

Technical data C60 SmartLine

Medium

Working medium: Corrosive, inert, gaseous and liquid media – in particular high-purity media – which have no negative impact on the physical and chemical properties of the body and diaphragm material.

Temperature

Media temperature: Valve body material PP-H (code G5, R5): -10 – 80 °C
Observe pressure/temperature diagram


Ambient temperature: 0 – 60 °C

Storage temperature: 0 – 40 °C

Pressure

Operating pressure: 0 – 6 bar

Pressure/temperature diagram:



Note: The temperature/pressure diagram is only an aid. The data refers to water as a working medium. A change of operating conditions or other media may result in deviations. In case of doubt, it is advisable to test the behaviour of the material under the definitive operating conditions in a test installation. Temperatures below 0 °C can have a negative influence on the actuation speed.

Cv values:

Actuator size	Connection size	DN	Connection type	Connection		
				Code	Tube	Pipe
2	1/2"	10	75, 77	34.2	-	
		15	20	-	82.5	
	3/4"	15	75	86.7	-	
		20	20	-	83.7	
	1"	20	20	-	171.7	
		20	75, 77	93.3	-	
		25	20	-	94.0	
3	1"	20	75, 77	183.3	-	
		25	20	-	233.3	
		25	78	-	233.3	
		25	75, 77	238.3	-	
		32	20	-	238.3	

Kv values in l/min

Vacuum: 400 mbar absolute

The service life of the valve may be affected if exposed to a greater vacuum or when valves are installed on the pump suction side.


Pneumatic actuator

Control pressure:


Control function	Actuator size	Control pressure
1	2	4 - 7 bar
	3	5 - 7 bar
2, 3	2, 3	max. 4 bar

Control pressure / operating pressure characteristics:

Control function 1 - normally closed (NC)



Control function 2 - normally open (NO)



Control air connection:

G 1/8

Filling volume:

Actuator size	Control function			
	Normally closed (NC)	Normally open (NO)	Double acting (closed) (DA)	Double acting (open) (DA)
2	24.0	39.0	39.0	24.0
3	56.0	88.0	88.0	56.0

Filling volume in cm³

Product conformities

Machinery Directive: 2006/42/EC

Dimensions C60 SmartLine

Food: FDA


EAC: The product is certified according to EAC.

Mechanical data

Flow direction: Optional

Dimensions C60 SmartLine


Flare connection (code 75, 77)



Actuator size	Connection size	ØB	ØB1	H	H1	L	L1	L2
2	1/2"	64.0	64.7	120.5	16.0	131.8	65.9	65.9
	3/4"	64.0	64.7	124.5	19.0	133.8	66.9	66.9
	1"	64.0	64.7	124.5	25.0	160.0	80.0	80.0
3	1"	80.0	86.0	160.5	25.0	180.0	90.0	90.0
	1 1/4"	80.0	86.0	160.5	25.0	192.0	96.0	96.0

Dimensions in mm


Butt weld spigot (code 20)



Actuator size	Connection size	ØB	ØB1	H	H1	L	L1	L2	Spigot (A)	
		DN							ød	ød1
2	15	64.0	64.7	124.5	19.0	131.0	65.5	65.5	20.0	16.2
	20	64.0	64.7	124.5	19.0	131.0	65.5	65.5	25.0	20.4
	25	64.0	64.7	124.5	19.0	145.0	72.5	42.5	32.0	26.0
3	20	80.0	86.0	160.5	25.0	166.0	83.0	83.0	25.0	20.4
	25	80.0	86.0	160.5	25.0	166.0	83.0	83.0	32.0	26.0
	32	80.0	86.0	160.5	25.0	172.0	86.0	86.0	40.0	32.6

Dimensions in mm


Union end (code 78)



Dimensions in mm/inch

Mounting dimensions

2/2-way valve (code D)




2/2-way valves (code D)

Actuator size	$\varnothing d$	A	B	C
2, 2E, 2 F, 2EF	5.5	61.5	31.0	40.0
3, 3E, 3 F, 3EF	6.5	78.0	39.0	56.0

Dimensions in mm

Mounting holes, round and slotted hole



Dimensions in mm

Dear customers,

In order to simplify installation, we are switching over the mounting holes to slotted holes for all valve sizes.

Due to the gradual changeover in manufacturing, you may therefore receive valve bodies with new slotted holes and also with the old, round boreholes during this phase.

We ask for your understanding in this matter.

Accessories



GEMÜ CFSTF

Service tool for flare union nuts

The GEMÜ CFSTF service tool is used for the assembly of GEMÜ CF flare union nuts in PFA, PVDF and carbon fibre reinforced PFA. A precisely defined torque can be achieved when using it in combination with a torque wrench.



GEMÜ 1098

Flaring mandrel

The GEMÜ 1098 flaring mandrel is an assembly tool for flare connections.



GEMÜ FlareStar

PFA fittings

Over 1,000 different types of fitting are produced under cleanroom conditions in compliance with DIN 16901-140. The fitting bodies are made of PFA, while the union nuts are made of PFA, PVDF or CPFA. We can also supply all standard market connections.



GEMÜ TubeStar

Tube

TubeStar is a product range comprising ultra-pure and standard PFA tubing. The tubes are particularly suitable for applications with high-purity media and other chemicals.



GEMÜ C67 STA

Service tool for actuators

Service tool for installation and removal of the central union nut.



GEMÜ Gebr. Müller Apparatebau GmbH & Co. KG
Fritz-Müller-Straße 6-8, 74653 Ingelfingen-Criesbach, Germany
Phone +49 (0) 7940 1230 · info@gemue.de
www.gemu-group.com